

Customer Info	Contractor:		Submitted By:			
	Address:		Phone:			
	City:	ST:	Mobile:			
	Job Name:		Job City:			
Building Information	Building Description:	Width:	Length:	Eave Height _{F/B} :		
		Roof Slope _{F/B} : :12		Dist to Ridge (from BSW):		
	Frame Type:	Gable	Single Slope	Lean-to	Beam & Column	# Int Columns:
	Endwall Type:	LEW: Bearing Fr	1/2 Load	Full Load	REW: Bearing Fr	1/2 Load Full Load
	Bay Spacings:	LEW to REW:				
	Design Information:	Design Code:		Occupancy Category:		
	Design Loads:	Live Load _{PSF} :	Wind Load _{MPH} :	Wind Exposure _{A-B-C-D} :	Total Collateral Load _{PSF} :	
	Deflection Criteria:	VERTICAL: Standard	Semi Brittle	Brittle	HORIZONTAL: Standard	Semi Brittle Brittle
	Primary Framing:	COLUMNS: Tapered		Straight		Straight Column Depth:
	Left Endwall:	Bypass	Flush	Frame & Columns Only	Col Spacing: _{L-R}	
	Right Endwall:	Bypass	Flush	Frame & Columns Only	Col Spacing: _{L-R}	
	Sidewall Girts:	Bypass Flush				
	Bracing:	Cable, Rod, Portal, Torsional, Fixed Base, Half Load		FSW	BSW	LEW REW
	Roof Panels:	24ga	26ga	Galvalume	Kynar	Sil Poly Color:
		KR2	KLM	KLS	RL RL+	Gutter & Downspouts
Wall Panels:	24ga	26ga	Galvalume	Kynar	Sil Poly Color:	
	KR2	KRP	KW	Stucco Choice	Other:	
Accessories	Walk Doors:	3070 Qty:	Closers Qty:	Panic-Lever Qty:	Glass Qty:	Type narrow/half:
		4070 Qty:	Closers Qty:	Panic-Lever Qty:	Glass Qty:	Type narrow/half:
		6070 Qty:	Closers Qty:	Panic-Lever Qty:	Glass Qty:	Type narrow/half:
	Premium Windows:	2060 Qtyfixed:	3030 Qtyfixed:	4040 Qtyfixed:	6030 Qtyfixed:	
		3030 Qtyslider:	4040 Qtyslider:	6030 Qtyslider:	Obscure Glass	
	Translucent Panels:	Roof Qty:	Wall Qty:	Insulated Qty:	Dektites: 1/4"-4" Qty:	4"-7" Qty: 7"-13" Qty:
Louvers:	3x3 Qty:	6x3 Qty:		9"x10' Vents: Galvalume Qty:	White Qty:	
Open Walls:	FSW		BSW		LEW REW	
Framed Openings:	FSW		BSW		LEW REW	
Notes:						
Alternates:	Alternate 1: Alternate 2: Alternate 3:					